

HD-S HEAVY DUTY STEEL



For decades, the **Arctic HD-S** has been the reason Canadians have found a parking spot. This go-to plow for commercial applications is constructed of 10 gauge hot-rolled steel and is reinforced with seven integrated vertical ribs for tremendous structural strength. The snow roll blade design not only reduces wear and increases fuel efficiency, it also prevents over-the-top snow loss without a snow deflector. Built for full-size vehicles and larger.

7 STRUCTURALLY INTEGRATED REINFORCING RIBS

 $for\ enhanced\ structural\ strength$



support the blade and leave ample room for an additional shock absorber, if one is desired

THREE 3/4" OPEN PINS

secure the blade to the quadrant and A-frame assembly, eliminating pin seizure, and easing pin replacement



QUIK*LINK® IV ATTACHMENT

10 GAUGE HOT-ROLLED STEEL for timeless strength

and durability

EXTREMELY DURABLE GALVANIZED ZINC COATING BONDS TO METAL

and gets into tough-toreach areas missed by other coating processes to provide superior rust protection

QUIK*LINK® III ATTACHMENT

STURDY REINFORCED ANGLE IRON A-FRAME AND QUADRANT ASSEMBLY

for sure connection to the undercarriage of the vehicle

6" DEFLECTOR

keeps snow down on the blade and away from the driver's windshield

> FULLY REVERSIBLE, HARDENED, HIGH CARBON STEEL CUTTING EDGE

lowers blade profile by exposing only 2" of blade at a time, and can be easily flipped when worn to start with a new edge

MEET THE REST OF THE ARCTIC PRODUCT LINE

arcticsnowplows.com













DISH-SHAPED SKID SHOES

improve surface clearance

while plowing forward

EXTRA-LARGE











HDXL-P

XHD-P

HDTE-P

HDVTE-P

HDVAW-P

HDSSTE-P

HD-S



HEAVY DUTY
STEEL



WHY CHOOSE STEEL?

Providing timeless performance and durability – Arctic's steel plow blades are constructed from 10 gauge hot-rolled steel, and are reinforced with integrated vertical ribs to form a single, tremendously strong structural unit. Blade curvature maximizes snow roll and handling, leading to reduced vehicle stress and improved fuel efficiency while minimizing over-the-top snow loss. All of Arctic's steel blades are dipped in galvanizing zinc coating for superior rust protection. Legendary strength and time-proven results, contact your Arctic Dealer for full details.



M3493 SERIES HYDRAULIC POWER UNIT

The M3493 electric hydraulic system, with a 1.5" x 6" lift cylinder offers proven performance and reliability in a compact size. This unit was built for the low mount lift frame and has an operating pressure of 2000 psi and the crossover relief valves are set at 3000 psi. This pump is compatible with all our control systems.



QUIK*LINK® III & IV MOUNTING KIT

Featuring an adjustable jack stand, our mounting systems allow you to remove the entire plow assembly as a single unit with the lift frame intact. Arctic's QUIK*LINK® III & IV system makes the already-simple mounting system even easier to use by replacing the two mounting pins with a simple single, spring-loaded locking bar.

ARCTIC HD-S SPECIFICATIONS

Plow Name	HD90-S	HD96-S	HD102-S	HD108-S
Length	90"	96"	102"	108"
Moldboard Height	27"	27"	27"	27"
Material (Steel)	10 Gauge	10 Gauge	10 Gauge	10 Gauge
Plowing Width (Full Angle)	78"	83″	88″	94"
Complete Weight	*657 lbs	*681 lbs	*708 lbs	*736 lbs
Mounting Type	Detachable	Detachable	Detachable	Detachable
Removable Lights	Yes	Yes	Yes	Yes

^{*} Weight does not include frame mounting kit

STANDARD CONTROLLER



HAND HELD

This ergonomic controller has 4 rubber faced buttons, and a float light in the middle. An automatic shut-off eliminates accidental use or drained batteries.

MPX WIRING



MODULE CONTROL SYSTEM

Easier installation, Universal Wiring Harness and Control Module to allow the use of different Arctic Snowplows simply by changing controllers. (note (*) Vehicles and plows must be MPX system compatible). Required for most newer vehicles.

OPTIONAL ACCESSORIES



SINGLE HALOGEN BULB (H9003)



LICENSE PLATE BRACKET



DUAL HALOGEN BULB (H7, H1)



POLY CUTTING EDGE



CURB GUARD



SHOCK ABSORBER



EXTEND. BL. GUIDES



PROWING EXTENSIONS

 $\textbf{QUIK*LINK}^{\textcircled{o}} \text{ is a registered trade-mark of Arctic Equipment Manufacturing Corporation}.$

LEGAL DISCLAIMER: Vehicles intended to be equipped with Arctic equipment must comply with the vehicle manufacturers' specifications for equipment application. Please consult your vehicle dealer before purchase and installation. The purchaser assumes all vehicle risk associated with the attachment and operation of Arctic equipment. Arctic reserves the right to change specifications without prior notification.

