

HDVTE-P

V TRIP EDGE POLY



THE "V" IS FOR VERSATILITY.

Each horizontally reinforced, steel backed poly section, comes with a double-acting 1 1/2" x 9" ram. The Arctic HDVTE-P full-grip joystick puts unprecedented control in the palm of your hand. Winter can visit, but it does so on your terms. Built for full-size vehicles and larger.

4 LASER-CUT, STEEL VERTICAL RIBS, AND 3 HORIZONTAL SUPPORTS

on each wing, back our frictionless poly moldboards with the strength of steel

DOUBLE LIFT CHAINS for extra lift strength

and safety

HOT-DIPPED GALVANIZED STEEL FRAME

provides added resistance to abrasion, water and rust, making our plows virtually maintenance free



QUIK*LINK® IV **ATTACHMENT**



throws snow further and faster resulting in less resistance and vehicle wear, and improved fuel economy

A 1 3/16" X 23 1/2" **GREASEABLE KINGPIN**

with a reinforced pin housing comprised of seven 2 1/2" x 5/8" wall bushings, provides tremendous strength

6" DEFLECTOR

keeps snow down on the blade and away from the driver's windshield



QUIK*LINK® III **FLARE KIT ATTACHMENT**

9" STROKE, DOUBLE-ACTING **CYLINDERS**

enable a full blade angle of 30 degrees in "V" and scoop position

1/2" X 6" HARDENED, HIGH **CARBON STEEL CUTTING EDGE**

with top hole bolt pattern



for optional bolt on wing kits

MEET THE REST OF THE ARCTIC PRODUCT LINE

arcticsnowplows.com























HD-P

HDXL-P

XHD-P

HDTE-P

HDVTE-P

HDVAW-P

HDSSTE-P

HD-S

HEAVY DUTY V TRIP EDGE POLY

WHY CHOOSE POLY?

Arctic's high density polyethylene moldboards combine the durable, slick characteristics of poly with advanced blade design mechanics to throw more of even the stickiest, wettest snow further and faster. This not only results in more snow being moved more quickly, it also minimizes forward resistance - meaning decreased wear on power trains and increased fuel economy. Contact your Arctic Dealer to learn more about the high-tech, low-maintenance benefits of poly.



M3500V SERIES HYDRAULIC POWER UNIT

The M3500V power unit has been designed around the proven M3593. The valve block has been changed to a 7 valve configuration to drive the double acting wing rams. This unit offers one of the highest power outputs in the industry, which means faster operation and less wear on the battery. Standard operating pressure is 1500 psi. Four crossover relief valves are set at 3000 psi.



QUIK*LINK® III & IV MOUNTING KIT

Featuring an adjustable jack stand, our mounting systems allow you to remove the entire plow assembly as a single unit with the lift frame intact. Arctic's QUIK*LINK® III & IV system makes the already-simple mounting system even easier to use by replacing the two mounting pins with a simple single, spring-loaded locking bar.

ARCTIC HDVTE-P SPECIFICATIONS

Plow Name	HDVTE96-P	HDVTE108-P
Length	96"	108"
Moldboard Height	29"	29"
Material	3/8" Poly	3/8" Poly
Plowing Width (Full Angle)	83"	94"
Complete Weight	*827 lbs	*866 lbs
Mounting Type	Detachable	Detachable
Removable Lights and Power Unit	Yes	Yes

^{*} Weight does not include frame mounting kit

STANDARD CONTROLLER



HAND HELD

This ergonomic controller has rubber faced buttons, and a float light in the middle. An automatic shut-off eliminates accidental use or drained

MPX WIRING



MODULE CONTROL SYSTEM

Easier installation, Universal Wiring Harness and Control Module to allow the use of different Arctic Snowplows simply by changing controllers. (note (*) Vehicles and plows must be MPX system compatible). Required for most newer vehicles.

OPTIONAL ACCESSORIES



SINGLE HALOGEN BULB (H9003)



LICENSE PLATE BRACKET



DUAL HALOGEN BULB (H7, H1)



3RD SPRING KIT



CURB GUARD



FLARE KIT



EXTEND. BL. GUIDES

QUIK*LINK® is a registered trade-mark of Arctic Equipment Manufacturing Corporation.

LEGAL DISCLAIMER: Vehicles intended to be equipped with Arctic equipment must comply with the vehicle manufacturers' specifications for equipment application. Please consult your vehicle dealer before purchase and installation. The purchaser assumes all vehicle risk associated with the attachment and operation of Arctic equipment. Arctic reserves the right to change specifications without prior notification.



Arctic Equipment Manufacturing Corporation

Toll Free 888 413 0019 www.arcticsnowplows.com