

BIGGER SNOW REMOVAL FOR SMALLER VEHICLES.

The clearing power of Arctic plows meets the new breed of agile, down-sized 4x4s. Featuring a scaled-down version of the QUIK*LINK® mounting system, a high density polyethylene skin and standard, sturdy Arctic construction, the **Arctic LD-P** offers many of the features of its bigger Arctic brothers. They'll call you small – until they call you for help.

5 LASER-CUT, STEEL REINFORCING RIBS

back our frictionless poly moldboard with the strength of steel

HOT-DIPPED GALVANIZED STEEL FRAME

provides added resistance to abrasion, water and rust, making our plows virtually maintenance free

1/4" SLICK POLYETHYLENE MOLDBOARD

throws snow further and faster resulting in less resistance and vehicle wear, and improved fuel economy

6" DEFLECTOR/ EXTENDER

keeps snow down in front of blade or adds height to the plow for deeper snow

3" DIAMETER TENSION SPRINGS

support the plow and are attached to a 1/4"-thick boxed quadrant that fixes to a double leg 2" X 2" boxed tubing A-frame with a 1" easy to remove greasable and bushed king bolt

1/4" X 4" NON-REVERSIBLE STEEL CUTTING EDGE

cuts and lifts hard packed snow and ice

MEET THE REST OF THE ARCTIC PRODUCT LINE

arcticsnowplows.com



LD-P



SD-P



HD-P




HDXL-P



XHD-P



HDTE-P



HDVTE-P



HD-VAW



HDSSTE-P



HD-S



PP-S

WHY CHOOSE POLY?

Arctic's high density polyethylene moldboards combine the durable, slick characteristics of poly with advanced blade design mechanics to throw more of even the stickiest, wettest snow further and faster. This not only results in more snow being moved more quickly, it also minimizes forward resistance – meaning decreased wear on power trains and increased fuel economy. **Contact your Arctic Dealer to learn more about the high-tech, low-maintenance benefits of poly.**



M3493 SERIES HYDRAULIC POWER UNIT

The M3493 electric hydraulic system, with a 1 1/2" x 6" lift cylinder offers proven performance and reliability. Compatible with the Hi Boy mounting kit, this power unit has one of the highest outputs in the industry. Standard operating pressures are 2000 psi and the crossover relief valves are set at 3000 psi. This pump is compatible with all of our control systems.



MOUNTING KIT


The mounting frame, a smaller version of the full-size QUIK*LINK® units, stands on an adjustable support leg and houses the M3493 pump in 3/8" thick laser cut plate.

ARCTIC LD-P SPECIFICATIONS

Plow Name	LD78-P	LD84-P
Length	78"	84"
Moldboard Height	18"	18"
Material	1/4" Poly	1/4" Poly
Plowing Width (Full Angle)	69 1/2"	75"
Complete Weight	*370 lbs	*380 lbs
Mounting Type	Detachable	Detachable
Removable Lights and Power Unit	Yes	Yes

* Weight does not include frame mounting kit

STANDARD CONTROLLER



HAND HELD

This ergonomic controller has 4 rubber faced buttons, and a float light in the middle. An automatic shut-off eliminates accidental use or drained batteries.

MPX WIRING



MODULE CONTROL SYSTEM

Easier installation, Universal Wiring Harness and Control Module to allow the use of different Arctic Snowplows simply by changing controllers. (note *) Vehicles and plows must be MPX system compatible. Required for most newer vehicles.

OPTIONAL ACCESSORIES



SINGLE HALOGEN BULB
(H9003)



DUAL HALOGEN BULB
(H7, H1)



EXTEND. BL. GUIDES



LICENSE PLATE BRACKET



EXTRA SPRING KIT



SHOE KIT

QUIK*LINK® is a registered trade-mark of Arctic Equipment Manufacturing Corporation.

LEGAL DISCLAIMER: Vehicles intended to be equipped with Arctic equipment must comply with the vehicle manufacturers' specifications for equipment application. Please consult your vehicle dealer before purchase and installation. The purchaser assumes all vehicle risk associated with the attachment and operation of Arctic equipment. Arctic reserves the right to change specifications without prior notification.

TOUGHER THAN A CANADIAN WINTER

Arctic Equipment
Manufacturing Corporation
Toll Free **888 413 0019**
www.arcticsnowplows.com

